

# X SERIES

## BUILD YOUR LEGACY



## STARTS WITH SHARING A PASSION

The FUJIFILM X-T30 combines a sleek mirrorless camera with next-generation image-making technology to meet the ever-increasing needs of content creators, regardless of their skill level. Boasting a new 26.1MP APS-C X-Trans CMOS 4 sensor and X-Processor 4 Quad-Core CPU, the X-T30 provides beginners, advanced amateurs, and professionals with fast auto-focus, strong face detection, and power to create high-resolution stills with notable sharpness and clarity. Combined with its increased sensitivity range up to ISO 51200 and the ability to record 10-bit, 4:2:2 DCI 4K video through the camera's HDMI port, the X-T30 is truly the perfect camera for releasing your creativity.

# FUJIFILM

# X-T30



X-T30

X-T30 and XF18-55mm lens

X-T30 and XC15-45mm lens

## X-T30 SPECIFICATIONS

<b>MODEL NAME</b>	FUJIFILM X-T30
<b>Number of effective pixels</b>	26.1 million pixels
<b>Image sensor</b>	23.5mm×15.6mm (APS-C) X-Trans CMOS 4 with primary color filter.
<b>Storage media</b>	SD memory card (~2GB) / SDHC memory card (~32GB) / SDXC memory card (~512GB)
<b>File format of still image</b>	JPEG: Exif Ver.2.3 *1, RAW: 14bit RAW (RAF original format) / RAW+JPEG
<b>Lens mount</b>	FUJIFILM X mount
<b>Sensitivity</b> Standard output Extended output	AUTO1 / AUTO2 / AUTO3 (up to ISO12800) / ISO160~12800 (1/3 step) ISO80/100/125/25600/51200
<b>Exposure control</b>	TTL 256-zone metering, Multi / Spot / Average / Center Weighted
<b>Exposure mode</b>	P (Program AE) / A (Aperture Priority AE) / S (Shutter Speed Priority AE) / M (Manual Exposure)
<b>Exposure compensation</b>	-5.0EV~+5.0EV 1/3EV step (Movie: -2.0EV~+2.0EV)
<b>Shutter type</b>	Focal Plane Shutter
<b>Movie recording</b> File format File size Frame rate Recording time	MOV (MPEG-4 AVC/H.264, Audio: Linear PCM / Stereo sound 24bit / 48KHz sampling) [DCI 4K(4096×2160)] 29.97p/25p/24p/23.98p 200Mbps/100Mbps up to approx. 10min [4K(3840×2160)] 29.97p/25p/24p/23.98p 200Mbps/100Mbps up to approx. 10min [Full HD(1920×1080)] 59.94p/50p/29.97p/25p/24p/23.98p 200Mbps/100Mbps up to approx. 15min. [Full HD(1920×1080)] 59.94p/50p/29.97p/25p/24p/23.98p 200Mbps/100Mbps up to approx. 15min. [Full HD(1920×1080) High speed rec.] 120p/100p 200Mbps(recording) up to approx. 6min. *For recording movies, use a SD memory card with UHS Speed Class 3 or higher. *Although movie recording will continue without interruption when the file size reaches 4GB, subsequent footage will be recorded to a separate file which must be viewed separately.
<b>Flash</b>	Manual pop-up flash (Super Intelligent Flash) Guide number : approx. 7 (ISO200 · m) / approx. 5 (ISO100 · m)
<b>LCD monitor</b>	3.0 inch, aspect ratio 3:2, approx. 1.04 millions dots touch screen color LCD monitor (approx. 100% coverage)
<b>Terminal</b> Digital interface HDMI output Other	USB Type-C (USB3.1 Gen1) HDMI micro connector (Type D) ø2.5mm, stereo mini connector (Microphone), Hot shoe, Synchronized terminal
<b>Dimensions</b>	118.4mm (W) x 82.8mm (H) x 46.8mm (D) / 4.66in. (W) x 3.26in. (H) x 1.84in. (D)
<b>Weight</b>	Approx. 383g (including battery and SD memory card) Approx. 333g (excluding battery and SD memory card)

VISIT [WWW.FUJIFILMUSA.COM](http://WWW.FUJIFILMUSA.COM) OR YOUR AUTHORIZED DEALER FOR MORE INFORMATION.

FUJIFILM and FUJINON are trademarks of FUJIFILM Corporation and its affiliates.  
© 2019 FUJIFILM North America Corporation and its affiliates. All rights reserved.

FUJIFILM